



SPECIFICATIONS

BTZ-42418-6

TYPE:----- DIGITAL
 DISPLAY: ----- 4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED
 CHARACTER HEIGHT: ----- 1.8" (45.72 mm)
 VISIBILITY: ----- 75 Ft. (22.86 METERS)
 POWER REQUIREMENTS:----- 110-240V 50~60Hz (**12vdc Switchig Power Supply**)
 FRAME: ----- ALUMINUM (**BLACK ANODIZED FINISH**)
 DIMENSIONS: ----- 6.25" x 64.25" x 1.38"
 WEIGHT: ----- 7 lbs.
 OPERATING TEMP.: ----- -17° TO 180° F
 HUMIDITY: ----- 0% TO 95% NON-CONDENSING
 OPERATING MODE:----- SYNCHRONIZED ZONES WITH ONE MASTER SET ZONE.



NEW 1 SEC YEAR ACCURATE (TCXO)

1.8", 2.5" and 4" DIGIT SIZE
 12 OR 24 HOUR FORMAT
 2 TO 24 ZONES
 NON GLARE LENS
 SUPER BRIGHT LEDs
 CUSTOM LETTERING TO YOUR SPECIFICATION
 ALUMINUM FRAME SURFACE MOUNT OR FLUSH
 10 YEAR LITHIUM BATTERY BACKUP (**Standard**)
 AUTOMATIC DAY LIGHT CORRECTION (**Standard**)
 INFRARED REMOTE CONTROL (**Standard**)
 ONE SEC A YEAR ACCURACY (TCXO) (**Standard**)

