

10:28

LOCAL

10:28

ZULU

SPECIFICATIONS

BTZ-42425-2

- TYPE: ----- DIGITAL
 DISPLAY: ----- 4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED
 CHARACTER HEIGHT: ----- 2.5"(63.5 mm) HR./MIN.
 VISIBILITY: ----- 150 Ft. (45.72 METERS)
 POWER REQUIREMENTS: 110-240V 50~60Hz (**SWITCHING POWER SUPPLY**)
 FRAME: ----- ALUMINUM (BLACK ANODIZED FINISH)
 DIMENSIONS: ----- 7.25" x 24.25" x 1.5"
 WEIGHT: ----- 9.5 lbs.
 OPERATING TEMP.: ----- -17° TO 190° F
 HUMIDITY: ----- 0% TO 95% NON-CONDENSING
 OPERATING MODE: ----- SYNCHRONIZED ZONES WITH ONE
 MASTER SET ZONE, AND IRR CONTROL.



NEW 1 SEC A YEAR ACCURATE (TCXO)

ALL CLOCKS USE THE DALLAS DS32 SERIES RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC A YEAR ACCURACY.



- 1.8", 2.5" and 4" DIGIT SIZE
- 12 OR 24 HOUR FORMAT
- 2 TO 24 ZONES
- NON GLARE LENS
- SUPER BRIGHT LEDS
- CUSTOM LETTERING TO YOUR SPECIFICATION
- ALUMINUM FRAME SURFACE MOUNT OR FLUSH
- 10 YEAR LITHIUM BATTERY BACKUP (**Standard**)
- AUTOMATIC DAY LIGHT CORRECTION (**Standard**)
- INFRARED REMOTE CONTROL (**Standard**)
- ONE SEC A YEAR ACCURACY (TCXO) (**Standard**)

