

10:28

LOCAL

18:28

ZULU

SPECIFICATIONS

BTZ-42440-2

- TYPE: ----- DIGITAL
- DISPLAY: ----- 4-DIGIT, 7 SEGMENT RED SUPER BRIGHT LED
- CHARACTER HEIGHT: ----- 4" (101.6 mm) HR. MIN.
- VISIBILITY: ----- 250 Ft. (76.2 METERS)
- POWER REQUIREMENTS:-- 100-240V 50~60Hz (12vdc Switching Power Supply)
- FRAME: ----- ALUMINUM (BLACK ANODIZED FINISH)
- DIMENSIONS: ----- 10.25" x 30.25" x 1.38
- WEIGHT: ----- 8.25 lb.
- OPERATING TEMP.: ----- -17° TO 182° F
- HUMIDITY: ----- 0% TO 95% NON-CONDENSING
- OPERATING MODE:----- SYNCHRONIZED ZONES WITH MASTER.


NEW 1 SEC A YEAR ACCURATE (TCXO)



ALL CLOCKS USE THE DALLAS DS32 SERIES RTC PARTS, AND OUR FIRMWARE CONTROL, TO GET THE ONE SEC A YEAR ACCURACY. **World's Most Accurate RTC**



- 1.8", 2.5" and 4" DIGIT SIZE
- 12 OR 24 HOUR FORMAT
- 2 TO 24 ZONES
- NON GLARE LENS
- SUPER BRIGHT LEDs
- CUSTOM LETTERING TO YOUR SPECIFICATION
- ALUMINUM FRAME SURFACE MOUNT OR FLUSH
- 10 YEAR LITHIUM BATTERY BACKUP (Standard)
- AUTOMATIC DAY LIGHT CORRECTION (Standard)
- INFRARED REMOTE CONTROL (Standard)
- ONE SEC A YEAR ACCURACY (TCXO) (Standard)



MOUNTING INSTRUCTIONS

